


 DOWNLIGHTS

DOWNLIGHT NEOPANEL


Downlight que destaca por su facilidad de instalación en techos de altura de empotramiento reducido. Uso muy adecuado en oficinas, espacios comerciales, zonas de paso, etc.



















Cod.	W	K	lm	Reg	Cert.	g	Ø mm	Ø Corte mm
7100020230	6	2.700	580	No	E	122	128	115
7100020231		3.000	600					
7100020232		4.000	600					
7100020233		5.500	650					
7100020234	12	2.700	1.200	No	E	193	170	155
7100020235		3.000	1.250					
7100020236		4.000	1.250					
7100020237		5.500	1.300					
7100020214	18	2.700	1.850	Sí (TRIAC)	E	325	224	210
7100020215		3.000	1.900					
7100020216		4.000	2.050					
7100020217		5.500	2.050					
7100020295	18	2.700	1.850	Sí (TRIAC)	D	325	224	210
7100020245		3.000	1.900					
7100020246		4.000	2.050					
7100020247		5.500	2.050					

-  2.700 K
-  3.000 K
-  4.000 K
-  5.500 K

7100020231



*Consultar en tabla de datos técnicos referencias regulables.

 IRC > 80	 120°	 TRIAC	 L80 35.000h	 SDCM < 6
 SWITCH OFF ON 100.000	 TIME OFF ON < 0,5 s	 +40 -20 °C	 CLASE II	 P.F. > 0,9
 220-240 VAC 50-60Hz	 E	 D	 IP 20	 IK 06
			 3 AÑOS GARANTÍA	